

## Model RBA4110-927



### Materials & Features

Set consists of a wall mounted Stainless Steel rail. Complete with slider, handset and 2.0m hose (1.5m available upon request). Water supply connection includes backflow prevention. Grab rail is accessible compliant when installed in accordance with AS1428.1-2009.

### Technical Detail

Rail:	#304 Stainless Steel, Satin, 32mm Dia
Hose:	2.0m
Inlet Connection:	DN 15mm (1/2") BSP
	Includes backflow prevention
Water Pressure:	150-500 kpa
Water Temperature:	50°C
Flow Rate:	8.0 LPM
WELS:	3 star

### Available Model

**RBA4110-927** Left Hand Accessible Compliant Shower 'T' Grab Rail with slider, handset and 2.0m hose

### Related Products

**RBA4110-926** Right Hand Accessible Compliant Shower 'T' Grab Rail with slider, handset and 2.0m hose

**RBA1110-750** Shower Mixer, Rectangle Plate

**RBA4110-999-005** Sliding Soap dish

### Installation

Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended.

**Note:** For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

