

## Model RBA4110-991



### Materials & Features

Shower Rail set consists of a wall mounted Stainless Steel 900mm shower grab rail complete with slider, handset and 2.0m hose (1.5m available upon request). Water supply connection includes backflow prevention. Grab rail is accessible compliant when installed in accordance with AS1428.1-2009 (Amdt. 2010) and local building codes.

### Technical Detail

|                    |                                       |
|--------------------|---------------------------------------|
| Rail:              | #304 Stainless Steel, Satin, 32mm Dia |
| Hose:              | 2.0m                                  |
| Inlet Connection:  | DN 15mm (1/2") BSP                    |
|                    | Includes backflow prevention          |
| Water Pressure:    | 150-500 kpa                           |
| Water Temperature: | 5 - 60°C                              |
| Flow Rate:         | 7.5 LPM                               |
| WELS:              | 3 star                                |

### Available Model

**RBA4110-991** Shower rail set with slider, handset and 2.0m hose

### Related Products

**RBA4110-990** Shower rail set with lever mixer, slider, handset and 2.0m hose

**RBA4000-075** 750mm straight rail

### Installation

Should be installed with RBA4000-075 to comply with AS1428.1-2009 (Amdt. 2010). Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended.

**Note:** For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

