

Model RBA8820-100



Materials & Features

Wall hung urinal is manufactured from heavy-gauge 1.6mm, type 304 stainless steel. External surface is satin finish. The Stainless Steel Urinal is extremely hygienic and highly vandal resistant. It is HEU (High Efficiency Urinal), because it has exceptional performance at low level flushing.

Technical Detail

Trap:	Low level P trap (by others)
Outlet:	50mm BSP
Inlet:	20mm Keeseal
Flush Volume:	1 Litre
Mounting Plate:	2mm Stainless Steel

Available Models

RBA8820-100

Wall Hung Urinal - Rear Supply

Installation

Ensure wall construction is capable of supporting the unit. Unit may be front or rear fixed to wall using furnished mounting frame [wall fixing anchors to be supplied by others]. A low level P trap should be used. Refer Installation Instruction for location of fixing points, trap outlet location, etc.

Note: For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

*All dimensions in mm

Front view dimensions: 330 (width), 570 (height), 200 (base width).

Side view dimensions: 430 (width), 270 TO RIM (height).

- ① Spreader
- ② Heavy Duty Mounting Bracket
- ③ Security Screws
- ④ Flushing Inlet Keeseal Adapter
- ⑤ Removable Strainer
- ⑥ 20mm Flush Pipe by Others
- ⑦ 50mm BSP Connection



As improvements in the design and performance of RBA products are continuous, specifications may be subject to change without notice. The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet. Revised 06/21 © 2021 by RBA Group TD/Model RBA8820-100/0621