

Model RBA1053-600

Materials & Features

Self-closing tap is designed for public washrooms, offices, schools, shopping centres, stadiums & airports. Single connection, tap will deliver cold or pre mixed water, single temperature only. Tap is activated by pushing the button, flow will cease when preset time is achieved. Tap cartridge is self-cleaning.

Technical Detail

Tap Body:	DZR Brass, Chrome plated
Inlet Connection:	15mm BSP (1/2"), Male
Flow Time:	4-10 seconds (non-adjustable)
Operating Pressure:	200 – 500 kPa
Supply:	Single temp (Max. 55°C)
Flow Rate:	4.5L per minute
Force to Activate:	20N @ 300 kPa



Available Models

RBA1053-600 6 Star [4.5Lpm] 'Rio' Self Closing Wall Tap

Related Products

RBA1053-688 'Rio-Plus' Self Closing Wall Tap with Integrated Isolation Valve

RBA1053-999-001 Vandal Resistance Kit

RBA1053-999-002 65mm Extension Kit

Note: For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

