

Model RBA2727-032



Materials & Features

Basin manufactured from stainless steel with all exposed surfaces in satin finish. Anti-microbial flexible bubbler with self-closing push button and non-squirt features. Stainless steel bubbler options available on request. Valve includes flow adjuster and strainer. Integral perforated drain for hygiene & ease of cleaning. Smooth radiused design eliminates sharp corners. Semi concealed pipework and fixings.

Technical Detail

Inlet Connection:	G½B
Outlet Connection:	40mm BSP waste
Water Pressure:	200 – 500 kPa
Basin & Housing:	1.2mm, type 304 Stainless Steel
Force to activate:	≤ 22N (0 N sensor activated model)
Refrigerant:	R-134a
Power:	220VAC, 50Hz, single phase
Capacity:	30L/hr drinking water at 10°C (incoming 27°C, ambient 32°C)

Available Models

- RBA2727-032** 'Enterprise' Water Cooler, 30L/hr
- RBA2725-032** 'Enterprise' Water Cooler, Sensor Activated

Related Products

- RBA2727-232** 'Enterprise' Dual Water Cooler, 30L/hr
- RBA8900-429** Accessible Wall Mounted Drinking Fountain
- RBA2730-032** 'Compact' Wall Mounted Drinking Fountain

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

