

## Models RBA2729-032 RBA2729-033



\*RBA2729-033 Shown.

### Materials & Features

Basin manufactured from stainless steel with all exposed surfaces in satin finish. Anti-microbial flexible bubbler with self-closing push button and non-squirt features. Stainless steel bubbler options available on request. Valve includes flow adjuster and strainer. Integral perforated drain for hygiene & ease of cleaning. Smooth radiused design eliminates sharp corners. Semi concealed pipework and fixings.

### Technical Detail

Inlet Connection:	1/2" BSP
Outlet Connection:	40mm BSP waste
Water Pressure:	200 – 500 kPa
Basin & Housing:	1.2mm, type 304 Stainless Steel
Force to activate:	≤ 22N
Refrigerant:	R-134a
Power Requirement:	220 VAC, 50Hz, single phase
Capacity:	30L/hr drinking water at 10°C (incoming 27°C, ambient 32°C)

### Available Models

- RBA2729-032** 'Contour' Water Cooler | 30L/hr
- RBA2729-033** 'Contour' Water Cooler | Stainless bubbler | 30L/hr
- RBA2729-132** 'Contour' Water Cooler | with glass filler | 30L/hr
- RBA2729-833** 'Contour' Heavy Duty Water Cooler | 2.0mm Stainless Steel | 30L/hr (round button)

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

