

Models RBA2729-232 RBA2729-233



*RBA2729-233 Shown.

Materials & Features

Basin manufactured from stainless steel with all exposed surfaces in satin finish. Anti-microbial flexible bubbler with self-closing push button and non-squirt features. Stainless steel bubbler options available on request. Valve includes flow adjuster and strainer. Integral perforated drain for hygiene & ease of cleaning. Smooth radiused design eliminates sharp corners. Semi concealed pipework and fixings.

Technical Detail

Inlet Connection:	G½B
Outlet Connection:	40mm BSP waste
Water Pressure:	200 – 500 kPa
Basin & Housing:	1.2mm, type 304 Stainless Steel
Force to activate:	≤ 22N
Refrigerant:	R-134a
Power Requirement:	220 VAC, 50Hz, single phase
Capacity:	30L/hr drinking water at 10°C (incoming 27°C, ambient 32°C)

Available Models

- RBA2729-232** 'Contour' Dual water cooler | 30L/hr
- RBA2729-233** 'Contour' Dual water cooler | Stainless bubbler | 30L/hr
- RBA2729-332** 'Contour' Dual water cooler | with glass filler | 30L/hr
- RBA2729-933** 'Contour' Dual Heavy Duty water cooler | 2.0mm Stainless Steel | 30L/hr (round button)

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

