


KB101 and KB111 REPLACEMENT STRAP INSTRUCTIONS

P/N 889-KIT

Hardware Supplied


Two 5/8" Phillips Pan Head Machine Screws




Tools Required:

Phillips Head Screwdriver or 1/8" Allen Wrench


1. Open Baby Changing Station. Remove the screws that secure the old strap to the unit. Discard old strap and screws.




2. Position the new strap on the unit with the buckle towards the right hand side of the unit.



3. Take one of the screws provided and insert it through the hole in the chafe tab and into the hole in the right hand side of the bed. Secure the screw into the screw insert.



4. Repeat step 3 for the other end of the strap by securing the strap to the left hand side of the bed.



5. Ensure that the strap is buckled. Clean up mess and close unit.



KB100 / KB101 REPLACEMENT SHOCK INSTRUCTIONS

P/N 874-KIT (KB100)

P/N 877-KIT (KB101)




Materials Supplied:

Shock

Tools Needed:

Flat Head Screwdriver

1. Remove the Baby Changing Station from the wall.
2. Turn the unit over so that you can access the shock on the back side of the station. On both ends of the shock there is a "C" clip that holds the shock onto the ball stud. To remove the shock, carefully slide a flat head screwdriver in-between the shock and the "C" clip. Once the tension on the "C" clip is removed you will be able to pull the shock off the ball stud. Repeat on both ends of the shock. Remove the shock completely from the unit.
3. Open the door of the Baby Changing Station all of the way. You will be able to locate the lower ball stud on the bottom of the door. Slide the thin end of the replacement shock down through the hole in the back of the unit.
4. Snap the replacement shock onto the lower ball stud. Make sure the shock is secured to the ball stud by slightly twisting the shock to make sure that it does not come unhooked.
5. Close the door of the Baby Changing Station all of the way. With the door completely closed compress the shock by pressing downward so that it can be attached to the upper ball stud. Snap the shock onto the ball stud. Twist the shock to make sure that it does not come unattached from the ball stud.
6. Open and close door of unit several times to make sure that the shock is functioning properly. Remount unit following the proper installation instructions that were provided with the unit. Once the unit is properly installed, check the shock several times by opening and closing the Baby Changing Station.





KB100, KB101, KB110, KB111 REPLACEMENT LINER LID INSTRUCTIONS

P/N 827-KIT, 828-KIT, 829-KIT, 830-KIT

Tools Required:

Phillips Head Screwdriver

1. Remove the changing station from the wall.
2. Locate the horizontal slot on the back of the unit next to the top of the shock.
3. Take the replacement liner dispenser lid and insert into the slot. The plastic lip should remain on the outside of the unit.
4. Open the unit to ensure the lid is positioned correctly.
5. Remount the unit to the wall.





KB100, KB101, KB102, and KB108 END CAP REPLACEMENT INSTRUCTIONS

P/N 387-KIT, 689-KIT, 692-KIT, 850-KIT

Tools Required:

Flat Head Screwdriver

1. If you still have one or both end caps in place, remove them by sliding a thin flat head screwdriver (or similar tool) between the head of the end cap and the side of the unit. Discard the old end caps.
2. Take one of the new end caps and insert it to the cylindrical recessed area located on one side of the unit. Push it in with hand pressure until it is snug.
3. Repeat step 2 for the other side of the unit.

