

**Note:** This product should be installed, by suitably qualified persons, in a fit for purpose application, to suitable materials, using suitable fixings and comply with any relevant codes. It should be inspected periodically for signs of wear and tear that may affect performance or safety.

Dimensions are subject to manufacturer's tolerance of +/-10mm. Rough-in should be completed with each fixture.

**Important:** Installation Instructions are subject to change without notice.

Please visit [www.rba.com.au](http://www.rba.com.au) for latest revision.



**RBA8862-100**

LEDGEBACK 'D' ROUND INSET BASIN



Model	RBA8862-100
Date	10/03/20
Doc#	ii/rba8862-100 /0320

Supercedes all previous



## COMPONENTS

Single Stainless Steel Inset Basin  
 Fixing Toggles  
 Plug & waste (40mm BSP outlet)

## NOTES

- 1) Installation should be carried out in accordance with all authority requirements, and as per these instructions.
- 2) Immediately on receipt, and before installation, check for marks or damage.
- 3) Designed for countertops up to 30mm thick.

## ROUGH IN

- 1) Mark the location of the basin, or as determined by the builder/project manager.
- 2) Provide cut out 430mm in diameter

## INSTALLATION

- 1) Attach fixing toggles to basin and fold back.
- 2) Mount basin and tighten fixing toggles.
- 3) Seal with silicon as required.
- 4) Attach Tapware (by others) and plug & waste to the basin.
- 5) Connect the wastes 40mm outlet to trap (provided by others) and drain away.

## INSTALLATION

