

Installation Template and Instructions
Bobrick Model B-527 Waste-Disposal Door
for 3/4" to 1-1/2" (19 to 38mm) Thick Countertops

1. This unit was designed for countertops measuring 3/4" to 1-1/2" (19 to 38mm) mounting thickness.
2. Minimum space requirement: 6" x 12-3/4" (152 x 324mm). 4-1/2" (114mm) minimum clearance below mounting surface required for downward swing of waste door.
3. Cut out countertop to the dimensions shown along the dotted line, making certain to position cutout in the location desired.
4. Apply sealant or caulk to underside of flange all around.
5. Place Waste Door into opening.
6. While holding unit down, snug against the countertop, bend (4) tabs up against underside of countertop. Secure with (4) screws provided.

BOBRICK BUILDING VALUE SINCE 1906

© 2017 by Bobrick Washroom Equipment, Inc.
Form No. 527-69 r10/10/17 Printed in U.S.A.

In the U.S.A.: BOBRICK WASHROOM EQUIPMENT, INC.
200 Commerce Drive, Clifton Park, New York 12065-1350 • Tel: (518) 877-7444 • FAX: 518-877-5029
6901 Tujunga Avenue, North Hollywood, California 91605-6213 • Tel: (818) 982-9600 • FAX: 818-503-9287
or email BobrickCustomerService@bobrick.com

In Canada: BOBRICK WASHROOM EQUIPMENT COMPANY
45 Rolark Drive, Scarborough, Ontario M1R 3B1 • FAX: (877) 423-8555