

MODELS

RBA Braille and Tactile Signs

RBA4330-0 Series

Stainless Steel Braille & Tactile Signs

RBA4330-8 Series

Polycarbonate Braille & Tactile Signs



RBA4330-021 shown



As improvements in the design and performance of RBA products are continuous, specifications may be subject to change without notice. The illustrations and descriptions herein are applicable to production as of the date of this Installation Instructions Sheet. Revised 05/22 © 2022 by RBA Group II/Model RBA Braille and Tactile Signs/0522

Selecting Location

Interpretive signage with raised lettering and graphics provide all the relevant information as required by the Building Code of Australia [D3.6] and fulfil the requirements of the Australian Standards [1428.1 – 2009].

Location Of Braille & Tactile Signs

1. Above the floor or ground surface.
2. Signs with single lines of characters must have the line tactile characters not less than 1250mm and not higher than 1350mm above the floor or ground surface.
3. Signs identifying rooms containing features or facilities listed in [D3.6] must be located:-
 - i. on the wall on the latch side of the door with the leading edge of the sign located between 50mm and 300mm from the architrave; and
 - ii. in the event of insufficient latch side dimension, a sign may be placed on the non-latch side of the door; and
 - iii. where [i] or [ii] is not possible, the sign may be placed on the door itself.
4. Signs identifying paths of travel must be placed so they are located directly ahead in the direction of travel. Where one wall continues in the direction of travel and the other forms a corner, the sign must be placed on the continuing wall.

Fixing

1. RBA recommends that signs be secured to surfaces using clear window/glass silicone.
2. A bead of silicone should be run around the circumference of the rear of the sign, approximately 10mm in from the edge. An additional 20mm Dia amount should also be applied to the centre of the rear of the sign.
3. The sign should be placed in the desired location and gently moved from side-to-side and up-and-down to allow the silicone to spread evenly over the rear of the sign. This will also naturally draw sign back to fixing surface.
4. RBA does not recommend screw fixing tactile signs

Note: This product should be installed, by suitably qualified persons, in a fit for purpose application, to suitable materials, using suitable fixings and comply with any relevant codes. It should be inspected periodically for signs of wear and tear that may affect performance or safety.

Dimensions are subject to manufacturer's tolerance of +/-10mm. Rough-in should be completed with each fixture.

Important: Installation Instructions are subject to change without notice.

Please visit **our websites** for latest revision.