

## Model RBA4150-229



### Materials & Features

Stainless steel 90° wraparound WC grab rail with backrest meets the requirements of AS1428.1 and can withstand an applied force of 1100N in any direction when installed correctly. Backrest is site adjustable upon installation to ensure accurate location. The snap flange cover conceals the fixings. Designed for installations with exposed cisterns.

### Technical Detail

Rail: 32mm [Dia], 304 Satin Stainless Steel  
 Backrest: White polyurethane, 40mm thick  
 Fixings: By others

### Available Model

**RBA4150-229** 90° Wraparound Grab Rail with Integrated Backrest, Right Hand

### Related Products

**RBA4150-230** 90° Wraparound Grab Rail with Integrated Backrest, Left Hand

**RBA4090-450** 90° Ambulant Grab Rail, Ambidextrous

**RBA4110-994** Shower Rail, Handset & Lever Mixer Kit

### Installation

Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended. Refer to local codes and Installation Instructions for location of fixing points, method of attachment, etc.

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

