

# 4 Star Stainless Steel Pans



## Learn more about RBA's new 4 Star WCs!

Tough, reliable, efficient and easy to maintain. Perfect for any commercial, public or council amenity project.

Find out more: [rba.com.au/4-star-wcs](http://rba.com.au/4-star-wcs)

## Model RBA5600-001-Series



### Materials & Features

External surface is satin finish. Internal bowl is bright polished and designed for hygiene, easy cleaning and scale resistance. Pre-drilled to suit security toilet seat. Suitable for front or rear fix. P-trap or S-trap variants available [see Available Models below].

### Technical Detail

Outlet Connection:	P or S-Trap 100mm OD
Pan Collar:	Standard [by others]
Bowl and Trap:	1.2mm, 304 Satin Stainless Steel
Housing:	1.5-2mm, 304 Satin Stainless Steel
Rear Fix Kit:	4 x M12 bolts [by others]
Front Fix Kit:	4 x M10 expansion bolts [by others]
Flush Pipe Configuration:	40mm PVC Flush Pipe + 60mm OD Keeseal [by others]

### Available Models

<b>RBA5600-001-602</b>	Standard config. pan, P-Trap, no seat
<b>RBA5600-001-603</b>	Standard config. pan, S-Trap, no seat
<b>RBA5600-001-600</b>	Ambulant config. pan, P-Trap, with seat & lid
<b>RBA5600-001-601</b>	Ambulant config. pan, S-Trap, with seat & lid
<b>RBA5600-001-800</b>	Accessible config. pan, P-Trap, with seat
<b>RBA5600-001-801</b>	Accessible config. pan, S-Trap, with seat



## Also Available

### 90° Wraparound Grab Rail & Backrest



Satin finish stainless steel brackets  
40mm white polyurethane pad  
Concealed mounting flanges and bracket cover  
Backrest is site adjustable

**RBA4150-229**


### 90° Grab Rail, Ambidextrous Ambulant



Satin finish stainless steel  
32mm dia, 57mm clearance,  
concealed fixings  
Two RBA4090-450's are required for compliant installations.

**RBA4090-450**

### 'Nautilus' Electronic Dual Flush Valve | Accessible



4 Star WELS with adjustable flush volume  
3.0mm Type 304 stainless steel plate  
AS1428.1 compliant

**RBA1882-100-007**

### Bobrick Double Toilet Roll Holder | Satin



Type 304 stainless steel  
Recessed version available  
AS1428.1 compliant  
315mm x 155mm

**B69997**