



Models RBA4115-936

Materials & Features

Set consists of a wall mounted stainless steel rail complete with slider, handset and 1.5m hose, with wall connection (includes backflow prevention). Grab rail is accessible compliant when installed in accordance with AS1428.1.

Technical Detail

Rail:	#304 Stainless Steel, Matte Black, 32mm Dia
Hose:	1.5m
Inlet Connection:	DN 15mm (1/2") BSP Includes backflow prevention
Water Pressure:	150-500 kPa
Water Temperature:	50°C Maximum
Flow Rate:	6.0 LPM
WELS:	5 Star
WELS Reg. Number:	S14913

Available Models

RBA4115-936

5 Star Shower T-Rail Kit | Right Hand | Matte Black

Related Products

RBA4115-937

5 Star Shower T-Rail Kit | Left Hand | Matte Black

RBA4115-950

5 Star Shower T-Rail Kit & Mixer | Right Hand | Matte Black

RBA4115-951

5 Star Shower T-Rail Kit & Mixer | Left Hand | Matte Black

Installation

Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended.

For best results, unit should be inspected and cleaned regularly as per the instructions in the RBA Product Warranty, Cleaning Care Guide, available on our websites.

Note: For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

