

## Model RBA1047-600



### Materials & Features

Self-closing tap is designed for public washrooms, offices, schools, shopping centres, stadiums & airports. Single connection, tap will deliver cold or pre mixed water, single temperature only. Tap is activated by pushing the button, flow will cease when preset time is achieved. Tap cartridge is self-cleaning.

### Technical Detail

Tap Body:	DZR Brass, Chrome plated
Inlet Connection:	15mm BSP (1/2")
Flow Time:	12-15 seconds (non-adjustable)
Operating Pressure:	200 – 500 kPa
Supply:	Single temp (Max. 55°C)
Flow Rate:	5.0LPM
WELS Reg.number:	T32958
WELS Rating:	6 Star
Locknut:	Brass
Force to activate:	20N @ 300 kPa

### Available Models

**RBA1047-600** 6 Star [5.0Lpm] Self Closing 'Gooseneck' Push Tap

### Related Products

**RBA1083-999-010** Heavy Duty Brass Locknut (add-on for installations in vandal prone areas)

**Note:** For Australia, Installation shall be in accordance with the PCA [Plumbing Code of Australia] and any relevant local authority requirements.

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

