



Models RBA4110-993 & RBA4110-994

Materials & Features

Modular stainless steel shower rail kit complete with lever mixer, slider, handset and 1.5m hose with wall connection [includes backflow prevention]. Grab rail is accessible compliant to AS1428.1 when installed alongside RBA4000-070.

Technical Detail

Rail:	900mm, 304 Satin Stainless Steel, 32mm [Dia.]
Hose:	1.5m
Inlet Connection:	DN 15mm [1/2"] BSP Includes backflow prevention
Water Pressure:	150-500 kPa
Water Temperature:	50°C Maximum
Flow Rate:	6.0 LPM
WELS:	5 Star
WELS Reg. Number:	S14913

Available Models

RBA4110-993

Shower Rail Kit | Satin

RBA4110-994

Shower Rail Kit & Mixer | Satin

Related Products

B819687

Bobrick Accessible Compliant Folding Shower Seat

RBA4171-101

Shower Curtain Rail + 2 Curtains & Hooks

RBA1110-750

oken Shower Mixer | Chrome | Rectangular Plate

Installation

Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended. Refer to local codes and Installation Instructions for location of fixing points, method of attachment, etc.

For best results, unit should be inspected and cleaned regularly as per the instructions in the RBA Product Warranty, Cleaning Care Guide, available on our websites.

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

