3

Straight Grab Rail | Bright Polished



Model RBA4008-Series

Materials & Features

Stainless steel straight grab rails, available in a range of lengths meet the requirements of AS1428.1-2009 (incl. Amdt. 2010) when installed correctly. The snap flange cover conceals the fixings.

Technical Detail

Rail: Fixings: SWL:

32mm [Dia], 304 Bright Polished Stainless Steel By others 1100N

Available Models

RBA4008-030	Bright Polished Straight Grab Rail 300mm
RBA4008-045	Bright Polished Straight Grab Rail 450mm
RBA4008-060	Bright Polished Straight Grab Rail 600mm
RBA4008-075	Bright Polished Straight Grab Rail 750mm
RBA4008-090	Bright Polished Straight Grab Rail 900mm
RBA4008-100	Bright Polished Straight Grab Rail 1000mm

*Additional sizes available upon request

Installation

Warning: Grab rails are no stronger than the anchors or walls to which they are attached and must be firmly secured in order to support the loads for which they are intended. Refer local codes and Installation Instructions for location of fixing points, method of attachment, etc.

*All dimensions in mm 89 32 L

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.



As improvements in the design and performance of RBA products are continuous, specifications may be subject to change without notice. The illustrations and descriptions herein are applicable to production as of the date of this Technical Data Sheet. Revised 04/21 © 2021 by RBA Group TD/Model RBA4008-Series/0421